



SANDBLASTING

Pressure model SBF/P



- 15 liter pressure pot for standard cabinets*
- 24-80 liter pressure pot for cabinets with cyclone*
- Robust cabinets with first brand components*
- Several types of opening for easy loading*

POSSIBILITY OF ADDING CYCLONE TO ALL MACHINES

*Built under EU directive: 2006/42/EU
Certification: PED Directive 97/23/EU*

*Possibility of using different type of abrasive media
Recommended compressor: 15-20 HP (1500-2000 litres/min)*



n° fabricante 1792 B



40 YEARS OF EXPERIENCE IN SURFACE TREATMENT

TECHNICAL FEATURES	SANDBLASTING CABINETS MODEL SBF/P					
	With lateral doors			Total frontal opening		
	SBF(+)/P 10x8	SBF(+)/P 12x9	SBF+/P 12x12	SBF/P 10x8 AF	SBF/P 12x9 AF	SBF/P 12x12 AF
Internal dimensions (mm)	1000x800x600 (735)	1200x900x600 (735)	1200x1200x835	1000x800x675	1200x900x675	1200x1200x675
Working internal capacity (mm)	950x720x600 (735)	1150x820x600 (735)	1150x1150x835	950x750x675	1150x855x675	1150x1150x675
Maximum weight on grid (kg)	100	100	100	100	100	100
Air consumption (litres/min)	1500-2000	1500-2000	1500-2000	1500-2000	1500-2000	1500-2000
Boron carbide nozzle (mm)	∅ 5	∅ 5	∅ 5	∅ 5	∅ 5	∅ 5
Internal lighting (W)	2X22	2X22	2X22	2X22	2X22	2X22
Engine-fan group (kW)	0,55	0,55	0,55	0,55	0,55	0,55
Filtering surface (m²)	10	10	10	10	10	10
Lateral doors	1 o 2 model(+)	1 o 2 model(+)	2	—	—	—